

USPTO PATENT FULL-TEXT AND IMAGE DATABASE[Home](#)[Quick](#)[Advanced](#)[Pat Num](#)[Help](#)[Bottom](#)[View Cart](#)

Searching 1976 to present...

Results of Search in 1976 to present db for:












((((AN/Dell AND configur\$) AND (selections OR options)) AND current) AND compar\$): 27 patents.

Hits 1 through 27 out of 27

[Jump To](#)[Refine Search](#)[AN/Dell and configur\\$ and \(selections or options\) an](#)

PAT. NO. Title

- Full
- 1 [6,847,858](#) [System and method for managing release of goods for packaging](#)
 - 2 [6,754,816](#) [Scalable environmental data calculation method customized by system configuration](#)
 - 3 [6,735,663](#) [Combination personal data assistant and personal computing device](#)
 - 4 [6,721,881](#) [System and method for determining if a display device configuration has changed by comparing a current indicator with a previously saved indicator](#)
 - 5 [6,721,817](#) [Original equipment manufacturer identification for configurable electronic hardware](#)
 - 6 [6,640,278](#) [Method for configuration and management of storage resources in a storage network](#)
 - 7 [6,598,223](#) [Method and system for installing and testing build-to-order components in a defined configuration computer system](#)
 - 8 [6,598,174](#) [Method and apparatus for storage unit replacement in non-redundant array](#)
 - 9 [6,578,013](#) [Method and system for communicating between supplier and customer devices](#)
 - 10 [6,560,726](#) [Method and system for automated technical support for computers](#)
 - 11 [6,519,762](#) [Method and apparatus for restoration of a computer system hard drive](#)
 - 12 [6,421,671](#) [Method and system for automated distribution of software](#)
 - 13 [6,331,936](#) [AC adapter for a module bay in a computer system](#)
 - 14 [5,974,544](#) [Method and controller for defect tracking in a redundant array](#)
 - 15 [5,943,029](#) [Method and apparatus to provide non-DDC monitor characteristics to system software](#)
 - 16 [5,680,539](#) [Disk array system which performs data reconstruction with dynamic load balancing and user-specified disk array bandwidth for reconstruction operation to maintain predictable degradation](#)

- Full*
- 17 5,676,567  Internal/external modular interface
 - 18 5,642,171  Method and apparatus for synchronizing audio and video data streams in a multimedia system
 - 19 5,619,723  System for scheduling read ahead operations if new request is sequential of last n last read requests wherein n is different on independent activities
 - 20 5,598,577  Computer system with automatic drive model ID recognition and drive type adaptation
 - 21 5,586,324  Computer system having system feature extension software containing a self-describing feature table for accessing I/O devices according to machine independent format
 - 22 5,579,528  Computer system employing docking bay with spring loaded connector pins and file coherency method
 - 23 5,530,960  Disk drive controller accepting first commands for accessing composite drives and second commands for individual diagnostic drive control wherein commands are transparent to each other
 - 24 5,506,977  Method and controller for minimizing reads during partial stripe write operations to a disk drive
 - 25 5,483,641  System for scheduling readahead operations if new request is within a proximity of N last read requests wherein N is dependent on independent activities
 - 26 5,473,761  Controller for receiving transfer requests for noncontiguous sectors and reading those sectors as a continuous block by interspersing no operation requests between transfer requests
 - 27 5,291,585  Computer system having system feature extension software containing a self-describing feature table for accessing I/O devices according to machine-independent format
-

[Top](#)[View Cart](#)[Home](#)[Quick](#)[Advanced](#)[Pat Num](#)[Help](#)